OSRAM

ONYX COPILOT

Flexible LED reading light



20 lm Pleasantly warm and glare-free light

37 cm 370 mm neck length powered via

cigarette lighter or with a plastic base for fixed connection

12 V + 24 V

The stylish light is suitable for both passenger cars (12 volt) and trucks (24 volt)



Precisely illuminating vehicle interiors

With its elegant and dynamic design, the ONYX COPILOT LED reading light achieves seamless integration into vehicle interiors. With its high flexibility, the reading light has a wide range of options for illuminating specific areas of the vehicle interior. The neck of the light is made of matt black silicon rubber and can be individually adjusted. The LED lifetime of ONYX COPILOT is extremely long: up to 20,000 hours! The Luminaire can be switched on/off and remain connected permanently. OSRAM provides a 2 year guarantee for this stylish light.

Product datasheet

Technical data

Product information

Order reference	ONYX M+7	
Application (Category and Product specific)	Flexible LED reading light	

Electrical data

Nominal wattage	0.50 W
Nominal voltage	12/24 V

Photometrical data

Color temperature	3200 K
Luminous flux	20 lm
Light color LED	Warm white

Dimensions & weight



Product weight	84.00 g
Length	0.0 mm

Colors & materials

Base color	Black
------------	-------

Lifespan

Guarantee	3 years

Additional product data

Connector to lamp	Cigarette lighter plug
-------------------	------------------------

Capabilities

Product datasheet

Technology	LED

Certificates & standards

Standards	CE
Type of protection	IP20

Country specific categorizations

Order reference	ONYX M+7
Order reference	ONTATIO

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Date of Declaration	21-08-2023	
Primary Article Identifier	4062172339377	
Declaration No. in SCIP database	In work	

Equipment / Accessories

- Matching mating plug AMP 626064-0
- Matching plugs: AMP 1217281-2, 63241-3, 62572-6 or 1217321-2

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172339377	ONYX COPILOT M+7	Folding carton box 1	110 mm x 35 mm x 290 mm	1.12 dm ³	165.00 g
4062172339384	ONYX COPILOT M+7	Shipping carton box 4	149 mm x 118 mm x 302 mm	5.31 dm ³	778.00 g
4062172339391	ONYX COPILOT M+7	Shipping carton box 32	491 mm x 317 mm x 329 mm	51.21 dm³	6934.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

Guarantee terms are available at www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Product datasheet

OSRAM