

XBO $\leq$ 450 W Double End



Areas of application

- Endoscopy
- Microscopy
- Surgical Headlamps
- Fiber Illumination
- Solar Simulation
- Imaging & Scanning

Product features and benefits

- High luminance / radiance with intense point source
- Color temperature approximately 6000 K (daylight) consistent through the life of the lamp
- High color rendering index: $R_a >$
- High arc stability
- High arc stability
- Hot restart capability
- Dimmable over a wide range
- Long lamp life





XBO XENON SHORT ARC LAMPS



XBO XENON SHORT ARC LAMPS



XBO XENON SHORT ARC LAMPS

Product family datasheet

Technical data

	Electrical Data			
Product description	Nominal wattage	Lamp voltage	Lamp current	Type of current
XBO 75 W/2	75 W	12...16 V ³⁾	4.9...5.9 A	DC
XBO 75 W/2 OFR ¹⁾	75 W	12...16 V ³⁾	4.9...5.9 A	DC
XBO 100 W OFR ¹⁾	100 W	12.8...14.4 V ³⁾	7.0...7.4 A	DC
XBO 150 W/4 ²⁾	150 W	17...21 V ³⁾	7.5 A	DC
XBO 150 W/1	150 W	17...21 V ³⁾	7.5 A	DC
XBO 150 W/CR OFR ¹⁾	150 W	15...18 V ³⁾	8.5 A	DC
	Operating Conditions			
Product description	Cooling			
XBO 75 W/2	Convection			
XBO 75 W/2 OFR ¹⁾	Convection			
XBO 100 W OFR ¹⁾	Convection			
XBO 150 W/4 ²⁾	Forced			
XBO 150 W/1	Forced			
XBO 150 W/CR OFR ¹⁾	Forced			

¹⁾ OFR = Ozone-free version
²⁾ Lamp uses a special quality of quartz glass, known as SUPRASIL, which – in comparison to conventional quartz – provides higher transmission below 250 nm
³⁾ Initial voltage range

Product family datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure in both the hot and cold state, XBO lamps must only be operated in appropriate enclosed casings. Always use the protective jackets supplied when handling these lamps. They may only be used as open lamps if appropriate safety measures are taken. More information is available on request or can be found in the leaflet included with the lamp or the operating instructions.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.