

# LEDDriving HL H4 Gen2



**Cool White color temperature of 6,000 K**

Better visibility thanks to daylight effect



**Exzellente Helligkeit**

More light allows to see farther and therefore react sooner. Signs, obstacles and hazards can be recognized sooner



**Very compact LED replacement for conventional H4 high and low beam lamps**

Reduced glaring thanks to an optimized light distribution



### Idealer LED-Ersatz für H4

With a color temperature of 6,000 K and a very compact design, the OSRAM LEDDriving HL retrofits provide an easy solution to upgrade car headlights with cool white LED light – providing a stylish look as well as superior brightness. The LED high and low beam lamps by OSRAM as replacement of conventional H4 lamps. With the latest LED technology and very compact design, these new lamps allow a high compatibility and an easy installation for an even wider range of car models. LEDDriving HL lamps are 12 V and 24 V compatible. The pair of lamps comes with a 5-year OSRAM guarantee and with a long service life. For precise guarantee conditions please refer to [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee). Please note: These products are not ECE-approved and must not be used on public roads in any exterior application. Use on public roads will invalidate both the operating license and insurance coverage. Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

## Technische Daten

### Produktinformation

Bestellnummer	9726CW
Product type (off-road vs. on-road)	Off-road $\pm$ H4
Application (Category and Product specific)	Mainly used for headlight/ fog light applications


### Elektrische Daten

Max. Leistungsaufnahme	15,40 W
Nennspannung	12 /24 V
Nennleistung	14,00 W
Prüfspannung	13,5 V
Leistungsaufnahme-Toleranz	$\pm$ 10 %

### Photometrische Daten

Lichtstrom	1517/1258 lm
Lichtstrom-Toleranz	$\pm$ 15 %
Farbtemperatur	6000 K
Lichtfarbe LED	Cool white

### Abmessungen & Gewicht



Länge	203,0 mm
Durchmesser	18,0 mm
Produktgewicht	110,00 g

### Lebensdauer

Lebensdauer B3	2500 h
Lebensdauer Tc	5000 h
Garantie	5 years

## Produktdatenblatt

### Zusätzliche Produktdaten

Socket (Normbezeichnung)	P43t
--------------------------	------

### Einsatzmöglichkeiten

Technologie	LED
-------------	-----

### Klassifikationen






Bestellnummer	9726CW
---------------	--------

### Verpackungsinformationen

Produkt-Code	Produkt-Bezeichnung	Verpackungseinheit (Stück pro Einheit)	Abmessungen (Länge x Breite x Höhe)	Volumen	Gewicht brutto
4052899605121	LEDiving HL $\triangle$ H4	Faltschachtel 2	136 mm x 56 mm x 162 mm	1.23 dm <sup>3</sup>	294.21 g
4052899605138	LEDiving HL $\triangle$ H4	Versandschachtel 8	240 mm x 148 mm x 182 mm	6.46 dm <sup>3</sup>	1302.00 g

Die genannten Produktnummern beschreiben die kleinste bestellbare Mengeneinheit. Eine Versandeinheit kann mehrere Einzelprodukte beinhalten. Als Bestellmenge verwenden Sie bitte das Ein- oder Mehrfache einer Versandeinheit.

### Downloads

Icon	Datei
	User instruction LEDiving HL
	Broschüren Sales Folder LEDiving replacement lamps (EN)
	Broschüren LEDiving Retrofits - Exchange overview (EN)
	Broschüren 618438_LEDiving RETROFIT application overview (EN)
	Video LEDiving HL LED high and low beam lamps 9726CW (H4) installation video in VW T5

#### Rechtliche Hinweise

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Detailed guarantee terms can be found at [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee).

#### Anwendungshinweis

## Produktdatenblatt

Für weitere Anwendungsinformationen beachten Sie bitte das Produktdatenblatt.

### Haftungsausschluss

Änderungen und Irrtümer vorbehalten. Vergewissern Sie sich, dass Sie immer den neuesten Stand verwenden.



# OSRAM