

LEDDriving HL H4 Gen2



Cool White color temperature of 6,000 K

Better visibility thanks to daylight effect



Superior brightness

More light allows to see farther and therefore react sooner. Signs, obstacles and hazards can be recognized sooner



Very compact LED replacement for conventional H4 high and low beam lamps

Reduced glaring thanks to an optimized light distribution



Suitable replacement for H4

With a color temperature of 6,000 K and a very compact design, the OSRAM LEDDriving HL retrofits provide an easy solution to upgrade car headlights with cool white LED light – providing a stylish look as well as superior brightness. The LED high and low beam lamps by OSRAM as replacement of conventional H4 lamps. With the latest LED technology and very compact design, these new lamps allow a high compatibility and an easy installation for an even wider range of car models. LEDDriving HL lamps are 12 V and 24 V compatible. The pair of lamps comes with a 5-year OSRAM guarantee and with a long service life. For precise guarantee conditions please refer to www.osram.com/am-guarantee. Please note: These products are not ECE-approved and must not be used on public roads in any exterior application. Use on public roads will invalidate both the operating license and insurance coverage. Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

Product family datasheet




Technical data

Product description	Product information			Electrical data			
	Order reference	Application (Category and Product specific)	Product type (off-road vs. on-road)	Power input	Nominal voltage	Nominal wattage	Test voltage
LEDriving HL \triangleq H4	9726CW	Mainly used for headlight/ fog light applications	Off-road \triangleq H4	15.40 W	12 /24 V	14.00 W	13.5 V

Product description	Photometrical data		Dimensions & weight	Lifespan		Additional product data	Capabilities
	Luminous flux	Luminous flux tolerance	Diameter	Lifespan B3	Lifespan Tc	Base (standard designation)	Technology
LEDriving HL \triangleq H4	1517/125 8 lm	$\pm 15\%$	18.0 mm	2500 h	5000 h	P43t	LED

Product family datasheet

Download Data

File	
	User instruction LEDriving HL
	Brochures Sales Folder LEDriving replacement lamps (EN)
	Video LEDriving HL LED high and low beam lamps 9726CW (H4) installation video in VW T5

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Detailed guarantee terms can be found at www.osram.com/am-guarantee.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

