

LEDDriving FL H8/H11/H16

LED replacement for conventional fog lamps



Kaltweiße Farbtemperatur von 6.000 K

Better visibility in foggy situations with a perfect color match for xenon and LED headlights. Signs, obstacles and hazards can be recognized sooner.



Exzellente Helligkeit

More light allows to see farther and therefore react sooner with reduced glaring thanks to an optimized light distribution



Ultra compact LED replacement for conventional H8 H11 and H16 fog lamps as socket solution

Easy installation with optimized compatibility



New OSRAM LED fog lamps to increase safety and performance

The latest generation of OSRAM LED fog lamps provides an even more convenient solution in order to replace and upgrade existing halogen fog lamps: With its ultra compact dimensions, the OSRAM LEDriving FL provides optimized compatibility as well as easy plug & play installation. Upgrading with state-of-the-art LED technology and a color temperature of 6,000 K for a stylish cool white look as well as improved visibility. These LED products offer a perfect color match with xenon and LED headlights and are for conventional H8, H11 and H16 fog lamps. A pair of new LEDriving FL lamps, comes with a 3-year OSRAM guarantee as well as with a long service life by less energy consumption. For precise guarantee conditions please refer to www.osram.com/am-guarantee. Please note: These products are not ECE-approved and must not be used on public roads in any exterior application. Use on public roads will invalidate both the operating license and insurance coverage. Some countries prohibit the sale and use of these products. Please contact your local distributor for information on your country.

Technische Daten

Produkt-Bezeichnung	Produktinformation			Elektrische Daten		
	Bestellnummer	Product type (off-road vs. on-road)	Application (Category and Product specific)	Nennspannung	Nennleistung	Prüfspannung
LEDDriving FL ≙ H8/H11/H16	67219CW	Off-road ≙ H8/H11/H16	Hauptsächlich für Scheinwerfer-/Nebelscheinwerferanwendungen gedacht	12.0 V	8.20 W	13,5 V

Produkt-Bezeichnung	Max. Leistungsaufnahme	Photometrische Daten		Abmessungen & Gewicht	Lebensdauer		Einsatzmöglichkeiten
		Lichtstrom-Toleranz	Lichtstrom	Durchmesser	Lebensdauer Tc	Lebensdauer B3	Technologie
LEDDriving FL ≙ H8/H11/H16	9,02 W	±15 %	720 lm	17.2 mm	5000 h	2500 h	LED

Produkt-Bezeichnung	Umwelt Informationen Informationen gemäß Art. 33 der EU Richtlinie (EC) 1907/2006 (REACH)		
	Datum der Deklaration	Primäre Erzeugnisnummer	SCIP Deklarationsnummer
LEDDriving FL ≙ H8/H11/H16	06-03-2024	4052899605046 4062172033312 4059089349544 4059089376885 4062172401890	In Vorbereitung

Downloads

Datei	
	Broschüren LEDriving Retrofits - Exchange overview (EN)

Rechtliche Hinweise

Diese Produkte haben keine ECE-Zulassung, d. h., sie dürfen am Auto an keiner Außenanwendung im öffentlichen Straßenverkehr eingesetzt werden. Benutzung auf öffentlichen Straßen führt zum Erlöschen der Betriebserlaubnis und Verlust des Versicherungsschutzes. In vielen Ländern sind der Vertrieb und die Benutzung dieser Produkte verboten. Bitte kontaktieren Sie Ihren lokalen Vertriebspartner, um nähere Informationen zu erhalten.

Detailed guarantee terms can be found at www.osram.com/am-guarantee.

Anwendungshinweis

Für weitere Anwendungsinformationen beachten Sie bitte das Produktdatenblatt.

Haftungsausschluss

Änderungen und Irrtümer vorbehalten. Vergewissern Sie sich, dass Sie immer den neuesten Stand verwenden.

