

# Product family datasheet

# LEDriving SL P21W YELLOW

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications

Available in Amber



Replaces conventional P21W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



# Suitable LED replacement for P21W

LEDriving SL P21W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional P21W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

# Product family datasheet

# Technical data

|                     | Electrica   | l Data          | Photometric Data |                 |                       |
|---------------------|-------------|-----------------|------------------|-----------------|-----------------------|
| Product description | Power input | Nominal voltage | Nominal wattage  | Test<br>voltage | Nominal luminous flux |
| LEDriving SL ≙ P21W | 1.8 W       | 12 V            | 1 W              | 13.5 V          | 50 lm                 |

|                     |                               | Physical Attributes & Dimensions | Lifetime Data  |                | Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh) |
|---------------------|-------------------------------|----------------------------------|----------------|----------------|--|
| Product description | Luminous<br>flux<br>tolerance | Diameter                         | Lifespan<br>B3 | Lifespan<br>Tc | Primary article identifier   |
| LEDriving SL ≙ P21W | ±25 %                         | 25.0 mm                          | 1500 hr        | 4000 hr        | 4062172152228  <br>4062172401357   |

| Product description | Candidate list substance 1 | CAS No. of substance | Safe use instruction   | Declaration no. in<br>SCIP database  |
|---------------------|----------------------------|----------------------|--|--|
| LEDriving SL ≜ P21W | Lead                       | 7439-92-1            | The identification of the Candidate List substance is sufficient to allow safe use of the article. | 558ba419-9f08-<br>4a0e-b0ad-<br>fa29ec684e7c  <br>f893b2c4-9d2c-4d79-<br>ac1d-e1942146ed73 |

# Product family datasheet

#### Download Data

#### File



User instruction

GPRS\_Safety symbols instructions



**Brochures** 

LEDriving Retrofits - Exchange overview (EN)

# Safety advice

Canbus compatibleColoured lamps for usage behind coloured glass

# Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

# **Application advice**

For more detailed application information and graphics please see product datasheet.

# Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.