


LEDDriving SL W21W YELLOW

Ideal replacement for any vehicle



Suitable for various vehicle exterior applications

Available in Amber



Replaces conventional W21W lamps

Easy upgrade to LED technology with plug & play solutions

Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



Suitable LED replacement for W21W

LEDDriving SL W21W replacement lamps offer a modern and intense light. These replacement lamps are suitable for all conventional W21W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Technical data

Product information

Order reference	7505DYP
Product type (off-road vs. on-road)	Off-road \triangleq W21W
Application (Category and Product specific)	Mainly used for signal/ indicator applications


Electrical data

Power input	2 W
Nominal voltage	12.0 V
Nominal wattage	1.40 W
Test voltage	13.5 V
Power input tolerance	$\pm 10\%$

Photometrical data

Luminous flux	55 lm
Luminous flux tolerance	$\pm 25\%$
Light color LED	Yellow

Dimensions & weight



Diameter	20.0 mm
Product weight	12.00 g
Length	47.5 mm

Lifespan

Lifespan B3	1500 h
Lifespan Tc	4000 h
Guarantee	4 years

Product datasheet

Additional product data

Base (standard designation)	W3x16d
-----------------------------	--------

Capabilities

Technology	LED ¹⁾
------------	-------------------

¹⁾ Light-emitting diode lamp

Country specific categorizations

Order reference	7505DYP
-----------------	---------

Environmental information


Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	09-02-2024
Primary Article Identifier	4062172149273 4062172401593
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	242dbb41-1832-44be-a6e6-faceaa8bb4e0

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172149273	LEDDriving SL \triangle W21W	Blister 2	135 mm x 95 mm x 18 mm	0.23 dm ³	36.00 g
4062172149280	LEDDriving SL \triangle W21W	Shipping carton box 10	119 mm x 109 mm x 151 mm	1.96 dm ³	215.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File	
	Brochures LEDriving Retrofits - Exchange overview (EN)

Safety advice

Product datasheet

Canbus compatible

Coloured lamps for usage behind coloured glass

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

The OSRAM logo is displayed in a bold, orange, sans-serif font.