

Product family datasheet

TYREinflate 200



Rapid Inflation Time

Inflate the tire to the desired pressure in ca. 4.5 minutes**



Wind-up Cable

Winding/unwinding mechanism for a neatly rolled up cable



Including three-piece adaptor kit

To inflate bicycles, balls and other inflatables



Rapid tyre inflator with wind-up cable

The OSRAM Tyreinflate 200 analogue tyre inflator inflates a 13" tyre from flat in up to 4.5 minutes**. It has a large on/off button for easy use. Its stable design keeps the inflator still while in use.

Powered from an in-car 12V socket, the Tyreinflate 200's long 3m power cable makes reaching all the tyres around the vehicles easier. Shows pressure readings in kPA, bar and PSI. Includes storage compartment for tyre valve caps when being used.

Comes with three-piece adaptor set for use with bicycle tyres, motorcycle tyres, balls and other inflatables.

**based on inflating a 13" tyre from flat to 2.41 BAR

Product family datasheet

Technical data

	Electrical Data	Additional product data	Capabilities	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)
Product description	Nominal voltage	Display Type	Fuse	Candidate list substance 1
TYRE inflate 200	11.1 V	Analogue	10 A	Lead

Product description	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
TYRE inflate 200	7439-92-1	The identification of the Candidate List substance is	2c7125da-b121- 4f3d-8c54- 1fc45a571265
		sufficient to allow safe use of the article.	91681add-0e23- 41d1-a9d2- 68596b3c0670

Product family datasheet

Download Data

	File
7	User instruction TYREinflate 200
D	Movie application TyreInflate How to Video (RU)
D	Product movie TyreInflate 200 Product Video (EN)
D	Product movie TyreInflate How to Video (EN)
D	Product movie TyreInflate How to Video (IT)
D	Video OSRAM TYREinflate 200: Rapid tyre inflator with wind-up cable
D	Video OSRAM TYREinflate How To: Change your vehicle's tyre pressure easily

Safety advice

Product won't exceed noise levels of more than 90 dB

Legal advice

CE and EAC compliant

- * for precise conditions please refer to: www.osram.com/am-guarantee
- ** based on inflating a 13" tyre from flat to 2.41 BARApplication advice:

For more detailed application information and graphics please see product datasheet.

Disclaimer:

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.