

LEDDriving HLM EASY GEN 2 H4/H19



Ultra compact LED replacement for conventional H4/H19 high and low beam lamps

“Socket Design” – no adapters and caps needed



Easy plug & play installation

Allowing a high compatibility and an easy installation



Cool White color temperature

Better visibility thanks to daylight effect

LED high and low beams lamps with plug & play system: no adapters and caps needed.

With its socket-based solution, the OSRAM LEDDriving HLM EASY GEN 2 retrofits provide an ultra-compact LED replacement of conventional H4/H19 high and low beam lamps with cool white LED light – providing a stylish look as well as superior brightness. It offers an easy plug & play installation with optimized compatibility: no adapters and caps needed! An optimized high-speed fan ensures active cooling – making a higher performance and high-level light output possible thanks to maximized heat dissipation.

The LEDDriving HLM EASY GEN 2 high and low beam lamps by OSRAM replace conventional halogen lamps, are 12V compatible and have a cool white color temperature. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for motorcycles with the respective halogen lamp types.

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.



Technische Daten

Produkt-Bezeichnung	Elektrische Daten			Photometrische Daten	
	Max. Leistungsaufnahme	Nennspannung	Nennleistung	Lichtstrom	Lichtstrom-Toleranz
LEDDriving HL EASY GEN 2 ≙ H4/H19	16.5W/12 V 6.5 W		22 W	1850/1500 lm	±25 %

Produkt-Bezeichnung	Physical Attributes & Dimensions	Lebensdauer	Umwelt Informationen Informationen gemäß Art. 33 der EU Richtlinie (EC) 1907/2006 (REACH)	
	Durchmesser	Lebensdauer Tc	Primäre Erzeugnisnummer	SCIP Deklarationsnummer
LEDDriving HL EASY GEN 2 ≙ H4/H19	21.5 mm	1000 hr	4062172420327	In Vorbereitung

Downloads

Datei	
	User instruction GPRS_Sicherheitssymbole Benutzerhinweise
	Brochures LEDriving Retrofits - Exchange overview (EN)

Sicherheitshinweise

Application advice:

For more detailed application information and graphics please see product datasheet and user manual.

Anwendungshinweis

Für weitere Anwendungsinformationen beachten Sie bitte das Produktdatenblatt.

Haftungsausschluss

Änderungen und Irrtümer vorbehalten. Vergewissern Sie sich, dass Sie immer den neuesten Stand verwenden.