Product datasheet

LEDinspect POCKET200

Inspectionlights



Multi-Angle positioning
180° flex and 360° twist. Extra slim design

200 Lumen
3 light functions: Up to 200lm-high Up to 80lm-low Up to 40lm-torchlight

2-year OSRAM Guarantee
Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.

Light is versatile

This high-quality inspection light from OSRAM is perfect for professional and private use. With three light functions - high with up to 200lm, low with up to 80lm and torch function with up to 40lm - there is the right light output for the task at hand. The compact design combined with multi-angle positioning -180° flex and 360° rotation- gives maximum flexibility and adjustability to give light exactly where needed. The integrated charge indicator shows the charging status of the rechargeable battery - up to 1,5 h operating time for high power or up to 3h for low power. This inspection light also contains magnets for hands-free work and easy attachment and is therefore ideal as a light for manual activities, car repairs and in everyday life. In addition, OSRAM grants a 2-year guarantee on this

© 2026, OSRAM GmbH. All rights reserved.

product*

© 2026, OSRAM GmbH. All rights reserved.

Technical data

Product information

Application (Category and Product specific)	LED inspection lights

General Product Information

Global order reference	LEDIL408

Electrical Data

Nominal wattage	2 W
Nominal voltage	3.7 V

Photometric Data

Color temperature	6200 K
Nominal luminous flux	200 lm
Light color LED	White

Physical Attributes & Dimensions



Product weight	120.00 g
Length	267.0 mm
Width	40.0 mm
Height	42.0 mm

LED module information

Number of LEDs per module	2

Colors & materials

Base color	Black / Orange

© 2026, OSRAM GmbH. All rights reserved.

Lifetime Data

Guarantee	2 years

Additional product data

Type of Battery	Rechargeable
Number of included batteries	1
Scope of battery	Yes
Battery	High-quality lithium-ion battery

Capabilities

Technology	LED

Certificates & standards

Standards	CE / EMC / MSDS / ROHS
IK Class	IK07

Logistical data

Watt hour per battery	2.96

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Candidate list substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe use instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration no. in SCIP database	fd47c268-ee86-4581-a702-e67ef0854f7a

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899623897	INSPECTION LAMP	Folding carton box 1	49 mm x 47 mm x 155 mm	0.36 dm^3	141.00 g
4052899624016	INSPECTION LAMP	Shipping carton box 6	167 mm x 159 mm x 116 mm	3.08 dm^3	931.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

© 2026, OSRAM GmbH. All rights reserved.

Download Data

	File
	User instruction GPRS_Safety symbols instructions
	User instruction LEDinspect POCKET 200
	Movie application LEDinspect Inspection Lights Trailer

Legal advice
Application advice:

For more detailed application information and graphics please see product datasheet and user instruction.*for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice
For more detailed application information and graphics please see product datasheet.

Disclaimer
Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, OSRAM GmbH. All rights reserved.