


## LEDDriving™ HL EASY XEN D3S



### Easy plug & play installation

Accurate mechanical compatibility – no adapters and/or caps needed



### Compact LED replacement for conventional high and low beam lamps

Same geometry as HID - allowing high compatibility with plenty of car models



### Cool White color temperature of 6,500 K

Better visibility thanks to daylight effect



### OSRAM's first Plug & Play off-road LED replacement for HID

With extra brightness the OSRAM LEDDriving HL EASY XEN ensures a compact LED replacement of conventional high and low beam lamps. These LED retrofit lamps are 12/24V compatible, come with a color temperature of 6,500 K and ensure a broader light distribution: more light allows to see better and therefore react sooner. The top OSRAM thermal management technology with integrated active cooling – a high speed fan - provides maximized heat dissipation for more powerful performances. Premium OSRAM quality and LED technology grant a long lifetime.

Please note: OSRAM LEDDriving HL EASY XEN change is recommended to be carried out by a professional.

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Technische Daten

| Produkt-Bezeichnung                     | Elektrische Daten      |              |              |              | Photometrische Daten |
|-----------------------------------------|------------------------|--------------|--------------|--------------|----------------------|
|                                         | Max. Leistungsaufnahme | Nennspannung | Nennleistung | Prüfspannung | Lichtstrom           |
| LEDDriving HL EASY XEN $\triangleq$ D3S | 42.0 W                 | 12 V         | 42 W         | 13,2 V       | 5000 lm              |

| Produkt-Bezeichnung                     | Lichtstrom-Toleranz | Physical Attributes & Dimensions | Lebensdauer    | Umwelt Informationen<br>Informationen gemäß Art. 33 der EU Richtlinie (EC) 1907/2006 (REACH) |                                              |
|-----------------------------------------|---------------------|----------------------------------|----------------|----------------------------------------------------------------------------------------------|----------------------------------------------|
|                                         |                     | Durchmesser                      | Lebensdauer Tc | Primäre Erzeugnisnummer                                                                      | Stoff der Kandidatenliste 1                  |
| LEDDriving HL EASY XEN $\triangleq$ D3S | $\pm 25\%$          | 13.8 mm                          | 5000 hr        | 4062172421461                                                                                | Kein deklarationspflichtiger Stoff enthalten |

| Produkt-Bezeichnung                     | SCIP Deklarationsnummer                      |
|-----------------------------------------|----------------------------------------------|
| LEDDriving HL EASY XEN $\triangleq$ D3S | Kein deklarationspflichtiger Stoff enthalten |

Downloads

| Datei                                                                             |                                                              |
|-----------------------------------------------------------------------------------|--------------------------------------------------------------|
|  | User instruction<br>GPRS_Sicherheitssymbole Benutzerhinweise |

Anwendungshinweis

Für weitere Anwendungsinformationen beachten Sie bitte das Produktdatenblatt.

Haftungsausschluss

Änderungen und Irrtümer vorbehalten. Vergewissern Sie sich, dass Sie immer den neuesten Stand verwenden.

