

## LEDDriving HL EASY GEN 2 H8/H9/H11/H16




### Ultra compact LED replacement for conventional high and low beam lamps

"Socket Design" – no adapters and caps needed



### Easy plug & play installation

Allowing a high compatibility and an easy installation



### Cool White color temperature

Better visibility thanks to daylight effect



### LED high and low beams lamps with plug & play system: no adapters and caps needed

With its socket-based solution, the OSRAM LEDDriving HL EASY GEN 2 retrofits provide an ultra-compact LED replacement of conventional high and low beam lamps with cool white LED light – providing a stylish look as well as superior brightness. It offers an easy plug & play installation with optimized compatibility: no adapters and caps needed! An optimized high-speed fan ensures active cooling – making a higher performance and high-level light output possible thanks to maximized heat dissipation.

The LEDDriving HL EASY GEN 2 high and low beam lamps by OSRAM replace conventional halogen lamps, are 12V compatible and have a cool white color temperature. With the latest LED technology and very compact design, these lamps allow a high compatibility and an easy installation for cars with the respective halogen lamp types. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.


# Familiendatenblatt

## Technische Daten

| Produkt-Bezeichnung                 | Elektrische Daten      |              |              |              | Photometrische Daten |
|-------------------------------------|------------------------|--------------|--------------|--------------|----------------------|
|                                     | Max. Leistungsaufnahme | Nennspannung | Nennleistung | Prüfspannung | Lichtstrom           |
| LEDiving HL EASY $\cong$ H8/H11/H16 | 26 W                   | 12 V         | 26 W         | 13,5 V       | 2000 lm              |

| Produkt-Bezeichnung                 | Lichtstrom-Toleranz | Physical Attributes & Dimensions | Lebensdauer    | Umwelt Informationen<br>Informationen gemäß Art. 33 der EU Richtlinie (EC) 1907/2006 (REACH) |                         |
|-------------------------------------|---------------------|----------------------------------|----------------|--|-------------------------|
|                                     |                     | Durchmesser                      | Lebensdauer Tc | Primäre Erzeugnisnummer  | SCIP Deklarationsnummer |
| LEDiving HL EASY $\cong$ H8/H11/H16 | $\pm$ 25 %          | 14.8 mm                          | 1000 hr        | 4062172426527  | In Vorbereitung         |

## Downloads

| Datei   |  |
|---|--|
|  | User instruction<br>GPRS_Sicherheitssymbole Benutzerhinweise |

### Anwendungshinweis

Für weitere Anwendungsinformationen beachten Sie bitte das Produktdatenblatt.

### Haftungsausschluss

Änderungen und Irrtümer vorbehalten. Vergewissern Sie sich, dass Sie immer den neuesten Stand verwenden.

