Product family datasheet

LEDinspect WEARABLE NECKLIGHT

Detachable Torches

High flexibility - can be placed around the neck, on the head, in the hand or on a magnetic surface

Up to 265 lm (high) & 130 lm (low)

Two light functions: Up to 265 lm (high) and up to 130 lm (low)

Approx. 1.5 hours charging time

With a charging time of only approx. 1.5 hours, this OSRAM light is quickly ready for use again

2-year OSRAM Guarantee*

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers.

Light is versatile

This rechargeable neck light with two individually detachable torches from OSRAM is perfect for professional and private use. With two light functions up to 265lm (high), 130lm (low) and an adjustable 90 degree angle, this offers different setting options for a variety of tasks. The LEDinspect Wearable Neck Light is particularly impressive with its great flexibility - it can be used around the neck, on the head, in the hand or on a magnetic surface. The rechargeable battery allows up to 3 hours of operation at high power or up to 4.5 hours at low power and with a charging time of only about 1.5 hours, this OSRAM lamp is

© 2026, OSRAM GmbH. All rights reserved.

also quickly ready for use again. A USB Micro B charging cable with two connections for the individual lamps to charge the lithium battery is included. In accordance with protection class IP54, this lamp has protection against the ingress of dust particles and against splashing water and has been tested for impact resistance in accordance with IK07. With a weight of only 115g and the flexible design, the product is easy to store and transport and is therefore ideal as a light for handicraft work, craft activities, car repairs and in everyday life. OSRAM also provides a 2-year guarantee*

*For precise conditions please refer to: www.osram.com/am-guarantee

© 2026, OSRAM GmbH. All rights reserved.

Product family datasheet

Technical data

	Product information	General Product Information	Electrical Data	
Product description	**Application (Category and Product specific)**	**Global order reference**	**Nominal wattage**	**Nominal voltage**
INSPECTION LAMP	LED inspection lights	LEDIL413	1 W	3.7 V

	Photometric Data			Physical Attributes & Dimensions
Product description	**Color temperature**	**Nominal luminous flux**	**Light color LED**	**Product weight**
INSPECTION LAMP	6500 K	265 lm	White	115.00 g

				LED module information
Product description	**Height**	**Length**	**Width**	**Number of LEDs per module**
INSPECTION LAMP	150 mm	158.0 mm	25.0 mm	1+1

	Colors & materials	Lifetime Data	Additional product data	
Product description	**Base color**	**Guarantee**	**Type of Battery**	**Number of included batteries**
INSPECTION LAMP	Black / Orange	2 years	Rechargeable	1

	Capabilities	Certificates & standards	Logistical data	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)
Product description	**Technology**	**IK Class**	**Watt hour per battery**	**Candidate list substance 1**
INSPECTION LAMP	LED	IK07	2.96	Lead

Product description	CAS No. of substance 1	Safe use instruction	Declaration no. in SCIP database
INSPECTION LAMP	7439-92-1	The identification of the Candidate List substance is sufficient to allow safe use of the article.	9b7cd37b-d0e8-4a84-abf2-d10e9bfc7dfe

© 2026, OSRAM GmbH. All rights reserved.

Product family datasheet

Download Data

	File
	User instruction LEDinspect Detachable Neck Light
	User instruction GPRS_Safety symbols instructions

Legal advice

Application advice:For more detailed application information and graphics please see product datasheet and the user instruction.*for precise conditions please refer to:

www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, OSRAM GmbH. All rights reserved.